



FranMar International Inc.



USA



Germany



Universal



Oceania



UK

A301-600W		
ITEMS	DC12V	DC24V
OUTPUT POWER	600W CONTINUE	
	1500W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10~15 V	DC 20~30 V
OUTPUT VOLTAGE	AC 100V,110V,120V,220V,230V,240V	
OUTPUT VOLTAGE REGULATION	+/- 5%	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW ALARM	DC 10+/- 0.5V	DC 20+/- 0.8V
BATTERY LOW SHUTDOWN	DC 9.5 +/- 0.5 V	DC 19.5 +/- 0.8 V
STANDBY CURRENT	< 0.5A	< 0.35A
EFFICIENCY	85~90%	
THERMAL PROTECT	60 +/- 0.5oC	
COOLING	WISDOM FAN START : WHEN THE OUTPUT REACH 200W	
	THE TEMPERTURE REACH 45oC, THE FAN WILL START AUTOMATICALLY	
PROTECTIONS	SOFT START	
	OUTPUT SHORT : SHUTDOWN	
	INPUT POLARITY REVERSE : BY FUSE	
	HIGH VOLTAGE INPUT : SHUTDOWN	
	LOW VOLTAGE INPUT : SHUTDOWN	
	OVERLOAD : SHUTDOWN	
	OVERTEMPATURE : SHUTDOWN AFTER BUZZER, KEEP SOUNDING FOR ONE MINUTE	
	BATTERY LOW : ALARM	
	INTELLIGENT FAN CONTROL	
	TROUBLE DISPLAY : LED	
FUSE	25 A x 3	20 A x 3
AC OUTLET	TWO AC OUTLET (TYPE 1,2)	
	ONE AC OUTLET (THE OTHER)	
SIZE(LxWxH)	213 x 200 x 70 MM	
WEIGHT	2 kgs	