



FranMar International Inc.



USA



Germany



Universal



Oceania



UK



A301-300W+USB		
ITEMS	DC12V	DC24V
OUTPUT POWER	300W CONTINUE	
	350W (30 MIN)	
	600W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10-15V	DC 20-30V
OUTPUT VOLTAGE	AC 100V,110V,120V,220V,230V,240V	
OUTPUT VOLTAGE REGULATION	+/- 5%	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW SHUTDOWN	DC 9.5+/- 0.5V	DC 19.5+/- 0.8V
STANDBY CURRENT	0.36A	0.2A
EFFICIENCY	90%	
USB POWER OUTPUT	DC 5V 500mA (MAX.)	
THERMAL PROTECT	60 +/- 0.5°C	
COOLING	WISDOM FAN START : WHEN THE OUTPUT REACH 100W OR THE TEMPERATURE REACH 40°C, THE FAN WILL START AUTOMATICALLY	
PROTECTIONS	SOFT START	
	OUTPUT SHORT : SHUTDOWN	
	INPUT POLARITY REVERSE : BY FUSE	
	HIGH VOLTAGE INPUT :SHUTDOWN	
	LOW VOLTAGE INPUT : SHUTDOWN	
	OVERLOAD : SHUTDOWN	
	OVERTEMPERATURE : SHUTDOWN AFTER BUZZER, KEEP SOUNDING FOR ONE MINUTE	
	BATTERY LOW : ALARM	
	INTELLIGENT FAN CONTROL	
	TROUBLE DISPLAY : LED	
FUSE	CIGARETTE PLUG :15A	CIGARETTE PLUG:10A
	BATTERY CORD:35A	BATTERY CORD:20A
AC OUTLET	TWO AC OUTLET (TYPE 1,2)	
	ONE AC OUTLET (THE OTHER)	
SIZE(LxWxH)	165x88x74 mm	
WEIGHT	0.9 kgs	