



FranMar International Inc.



USA



Germany



Universal



Oceania



UK

A301-2500W		
ITEMS	DC12V	DC24V
OUTPUT POWER	2500W CONTINUE	
	5000W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10~15 V	DC 20~30 V
OUTPUT VOLTAGE	AC 100V,110V,120V,220V,230V,240V	
OUTPUT VOLTAGE REGULATION	+/- 5%	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW ALARM	DC 10+/- 0.5V	DC 21+/- 0.8V
BATTERY LOW SHUTDOWN	DC 9.5 +/- 0.5 V	DC 20 +/- 0.8 V
STANDBY CURRENT	< 0.7A	< 0.6A
EFFICIENCY	85~90%	
THERMAL PROTECT	60 +/- 0.5oC	
COOLING	WISDOM FAN START : WHEN THE TEMPERTURE REACH 45oC,	
	THE FAN WILL START AUTOMATICALLY	
PROTECTIONS	SOFT START	
	OUTPUT SHORT : SHUTDOWN, AUTO RESUME AFTER SOLVE	
	SHORT PROBLEM	
	INPUT POLARITY REVERSE : BY FUSE	
	HIGH VOLTAGE INPUT : SHUTDOWN	
	LOW VOLTAGE INPUT : SHUTDOWN	
	OVERLOAD : SHUTDOWN	
	OVERTEMPERTURE : SHUTDOWN	
	BATTERY LOW : ALARM	
	INTELLIGENT FAN CONTROL	
	TROUBLE DISPLAY : LED	
	VOLTAGE/AMPS DISPLAY	
FUSE	30 A x 12	15 A x 12
AC OUTLET	TWO AC OUTLET	
SIZE (LxWxH)	430 x 210 x 159 mm	
WEIGHT	8.7 kgs	