

A601- 1000W SPEC

ITEMS	DC12V	DC24V
OUTPUT POWER	1000W CONTINUE 1200W (30 MIN) 2400W FOR SURGE OUTPUT	
INPUT VOLTAGE	DC 10-15V	DC 20-30V
OUTPUT VOLTAGE	AC 100V,110V,120V,220V,230V,240V	
OUTPUT VOLTAGE REGULATION	+/- 5%	
OUTPUT WAVEFORM	MODIFIED SINE WAVE	
OUTPUT FREQUENCY	50 OR 60 HZ	
BATTERY LOW ALARM	DC 10+/- 0.5V	DC 21 +/- 0.8V
BATTERY LOW SHUTDOWN	DC 9.5+/- 0.5V	DC 20+/- 0.8V
STANDBY CURRENT	<0.45A	<0.3A
CHARGER CURENT	3.5A	2A
TRANSFER TIME	10m SEC	
EFFICIENCY	85~90%	
THERMAL PROTECT	60 +/- 0.5℃	
COOLING	WISDOM FAN START : WHEN THE TEMPERATURE REACH 45℃,THE FAN WILL START AUTOMATICALLY	
PROTECTIONS	※SOFT START ※OUTPUT SHORT : SHUTDOWN,AUTO RESUME AFTER SOLVE SHORT PROBLEM ※INPUT POLARITY REVERSE : BY FUSE ※HIGH VOLTAGE INPUT :SHUTDOWN ※LOW VOLTAGE INPUT : SHUTDOWN ※OVERLOAD : SHUTDOWN ※OVERTEMPERATURE : SHUTDOWN ※BATTERY LOW : ALARM ※INTELLIGENT FAN CONTROL ※TROUBLE DISPLAY : LED	
FUSE	30A*5	15A*5
AC OUTLET	THREE AC OUTLET (TYPE 1,2) TWO AC OUTLET (THE OTHER)	
SIZE(L*W*H)	380*210*85 mm	
WEIGHT	4.8 kgs	

