

5 Watts SIP Type DC - DC Converter

FEATURES

- ◆ 5W Regulated Output Power
- ◆ High Efficiency
- ◆ Internal Filtering
- ◆ SIP8 Package
- ◆ UL 94V-0 Potting Material
- ◆ 100% Burn In
- ◆ MTBF > 400,000 Hours
- ◆ 3 Years Warranty

SPECIFICATIONS

Input Voltage Range	2:1
Input Filter	Capacitor Type
Voltage Set-Point Accuracy	± 2% max.
Temperature Coefficient	± 0.05%/°C
Ripple & Noise (20MHz BW)	100mVp-p max.
Line Regulation ¹	± 0.5% max.
Load Regulation ²	± 0.5% max.
3.3Vout	± 1.0% max.
Minimum Load	20% of full load
Short Circuit Protection	Continuous
Efficiency	79% min.
Isolation Voltage ³	1500VDC
Isolation Resistance	10 ⁹ Ω min.
Switching Frequency	100KHz min.
Isolation Capacitance	80pF max.
Operating Temperature	-40°C To +60°C
Storage Temperature	-55°C To +105°C
Cooling	Free-Air Convection
Case Material	Non-Conductive Plastic
Case Size	21.8*9.20*11.1 mm
Weight	4.8 g
Packing	23 pcs / tube ; 2300 pcs per carton

Note:

(1) Line Regulation is for 1.0% change in Input Voltage.

(2) Load Regulation is for output Load current change from 20% to 100%.

(3) 1500VDC for 10 seconds



Model Number	Input Voltage (VDC)	Output Voltage (VDC)	Output Current (mA)	EFF. % (min.)
DP05-x0	see note	3.3	1200	80
DP05-x1	see note	5	1000	81
DP05-x2	see note	12	471	85
DP05-x3	see note	15	333	84
DP05-x4	see note	± 5	± 500	79
DP05-x5	see note	± 12	± 208	81
DP05-x6	see note	± 15	± 167	82


Note:

x=1, input range 9-18VDC

x=2, input range 18-36VDC

x=3, input range 36-75VDC

MECHANICAL DRAWING (Unit: mm[inch])



Pin Connection

Pin#	Single	Dual
1	Vi-	Vi-
2	Vi+	Vi+
3	Remote	On/Off
5	NC	NC
6	Vo+	Vo+
7	Vo-	Com.
8	NC	Vo-